

CLAIMS

1. A coaxial connector device comprising a first and a second connector section with longitudinal axes (F, E), said first section comprising a coaxially disposed first inner terminal (2) for releasable mechanical and electrical connection to a coaxially disposed second inner terminal (7) of the second connector section, **c h a r a c -**
5 **t e r i s e d** in that said first (2) and second (7) inner terminals are provided with mutually corresponding contact means (2B, 2C; 7A) for the establishment of a releasable contact between said first and second inner terminals (2, 7).
- 10 2. Connector device according to claim 1, **c h a r a c t e r i s e d** in that said contact means comprises a male end on said first inner terminal (2) and a corresponding female end on said second inner terminal (7).
- 15 3. Connector device according to claim 1, **c h a r a c t e r i s e d** in that said contact means comprises a female end on said first inner terminal (2) and a corresponding male end on said second inner terminal (7).
- 20 4. Connector device according to claim 1, **c h a r a c t e r i s e d** in that said longitudinal axes (F, E) extend at an angle (α) relative to each other.
5. Connector device according to claim 4, **c h a r a c t e r i s e d** in that said angle (α) is substantially 90 degrees.
- 25 6. Connector device according to claim 1, **c h a r a c t e r i s e d** in that said unitary body (1) is fixably attached to said shell (6) by an interlocking of a locking ridge (12) with a locking groove (13).
- 30 7. Connector device according to claim 1, **c h a r a c t e r i s e d** in that said unitary body (1) is fixably attached to said shell (6) by a screw thread (12) screwed into a receiving spindle (13).
8. Connector device according to claim 1, **c h a r a c t e r i s e d** in that said inner terminal (2) has at least one male end.

9. Connector device according to claims 1 and 8, **characterised** in that said inner terminal (2) has at least one female end.

5 10. Connector device according to claim 1, **characterised** in that said inner terminal (7) has at least one male end.

11. Connector device according to claim 1 and claim 10, **characterised** in that said inner terminal (7) has at least one female end.

10 12. Connector device according to claim 8, **characterised** in that said inner terminal (2) has a tapered male end (2A).

15 13. Connector device according to claim 8, **characterised** in that said inner terminal (2) has a gap (2C) for the accommodation of the lateral inner terminal (7).

14. Connector device according to claim 8, **characterised** in that said inner terminal (2) has an integral perpendicular node (2B).

20 15. Connector device according to claim 10, **characterised** in that said lateral inner terminal (7) has a fingered node-receiving end (7A).

25 16. Connector device according to claim 1, **characterised** in that an O-ring (11) forms a moisture-proof seal between said unitary body (1) and said shell (6).